



F.M.I. S.p.A.- Via Taranto, 10/12 – 25036 - S.Pancrazio di Palazzolo S/Oglio (BS) Italy  
Tel.+39-0307386033 Fax+39-0307386035

[www.fmi-spa.com](http://www.fmi-spa.com)

## **FLEXPACK 2600D**

### **PRODUCT**

### **REFERENCE**

### **DESCRIPTION:**

FLEXPACK 2600D is a soft, flexible packing constructed by x-braiding pure PTFE yarn

### **COLOUR:**

WHITE

### **SERVICE:**

FLEXPACK 2600D can be used in valve or static applications handling most chemical media.

It is especially used for more applications involving concentrated acids or where non-contamination of the product is required. The relatively soft and conformable nature of 26D enables sealing to be achieved with minimum gland pressure. Typical sealing applications include aggressive chemicals, foodstuffs and pharmaceuticals.

Temperature range: -85°C / +260°C

Maximum pressure: 70 bar

Maximum shaft speed: 3 m/s

pH: 0-14

### **AVAILABILITY:**

The following square section material is available in coils or as pre-formed rings:

3.0, 4.0, 5.0, 6.5, 8.0, 9.5, 12.5, 14.0, 16.0, 19.0, 22.0, 25.0 mm

We can supply other sizes upon request.

**Quality system accredited ISO 9001:2000**